

MICROMETER CALIBRATION

GAUGE BLOCK SET

DIN ISO 3650

- Garde 0 or Grade 1 (optional)
- 10 pcs rectangular blocks and 1 optical flat
- 1 Optical Flat which allows checking anvil faces at half rotations of spindle for measuring flatness

MADE OF CERAMIC



Unit:mm

Code	Grade	Contents
6110-1211	0	The size of each gauge block 2.5,5.1,7.7,10.3,12.9,15.0,17.6,20.2,22.8,25.0; 1 pc optical with a flat glass $\phi 30$
6110-1405	1	The size of each gauge block 2.5,5.1,7.7,10.3,12.9,15.0,17.6,20.2,22.8,25.0; 1 pc optical with a flat glass $\phi 30$

MADE OF STAINLESS STEEL



Unit:mm

Code	Grade	Contents
6111-1210	0	The size of each gauge block 2.5,5.1,7.7,10.3,12.9,15.0,17.6,20.2,22.8,25.0; 1 pc optical with a flat glass $\phi 30$
6111-1211	1	The size of each gauge block 2.5,5.1,7.7,10.3,12.9,15.0,17.6,20.2,22.8,25.0; 1 pc optical with a flat glass $\phi 30$

OUTSIDE MICROMETER

WITH ADJUSTABLE ANVILS

DIN 863

- Wide measuring range with adjustable extension anvil collars
- Strictly made in accordance with DIN 863
- With ratchet stop for constant pressure
- Spindle thread hardened, ground and lapped for ultimate accuracy
- Clear graduations laser-etched on satin chrome finish for easy reading
- With spindle lock

Unit:mm

Code	Range	Graduation	L	H	Lo/L1	Accuracy
4800-0005	300-400	0.01	410	215	325/375	0.011
4800-0010	400-500	0.01	510	265	425/475	0.013
4800-0015	500-600	0.01	610	315	525/575	0.015
4800-0020	600-700	0.01	710	365	625/675	0.016
4800-0025	700-800	0.01	810	415	725/775	0.018
4800-0030	800-900	0.01	910	465	825/875	0.02
4800-0035	900-1000	0.01	1010	515	925/975	0.022
4810-0005	12"-16"	0.001"	410	215	325/375	0.0004"
4810-0010	16"-20"	0.001"	510	265	425/475	0.0005"
4810-0015	20"-24"	0.001"	610	315	525/575	0.0006"
4810-0020	24"-28"	0.001"	710	365	625/675	0.0006"
4810-0025	28"-32"	0.001"	810	415	725/775	0.0007"
4810-0030	32"-36"	0.001"	910	465	825/875	0.0008"
4810-0035	36"-40"	0.001"	1010	515	925/975	0.00085"

