

Fühlhebelmessgerät

- DIN 2270
- HM-Kugel 2 mm
- Einspannschaft Ø 8 mm
- Tastarm automatisch umkehrbar
- inkl. Etui



281-11

Horizontal/horizontal

> mm <	mm	Ø mm	No.
0,8	0,01	32	281-11
0,2	0,002	32	281-21
0,8	0,01	40	281-31
0,2	0,002	40	281-41

Dial test indicator

- DIN 2270
- carbide ball 2 mm
- stem diameter 8 mm
- autoally reversing arm
- incl. box



281-51

Vertikal/vertical

> mm <	mm	Ø mm	No.
0,8	0,01	32	281-51
0,2	0,002	32	281-61
0,8	0,01	40	281-71
0,2	0,002	40	281-81

Fühlhebelmessgerät

- Werksnorm
- Messeinsatz Stahl, Ø 2 mm
- Einspannschaft Ø 4 mm und 8 mm
- Tastarm automatisch umkehrbar
- inkl. Etui



281-10



281-60

Dial test indicator

- factory standard
- probe tip steel, Ø 2 mm
- stem diameter 4 mm and 8 mm
- autoally reversing arm
- incl. box

Horizontal/horizontal

> mm <	mm	Ø mm	No.
0,8	0,01	32	281-10
0,2	0,002	32	281-20
0,8	0,01	40	281-30
0,2	0,002	40	281-40

Vertikal/vertical

> mm <	mm	Ø mm	No.
0,8	0,01	32	281-50
0,2	0,002	32	281-60
0,8	0,01	40	281-70
0,2	0,002	40	281-80

Tastspitzen / touch probes

für Messbereich for range	Ø mm	L mm	Material material	No.
0,8mm	2	14,3	Vollhartmetal / carbide	281-02
0,8mm	2	14,3	Stahl / steel	281-05
0,2mm	2	13,5	Vollhartmetal / carbide	281-04
0,2mm	2	13,5	Stahl / steel	281-03
0,2mm	1	13,5	Stahl / steel	281-06

> mm < Messbereich Range
 Ablesung Reading
 Gehäusedurchmesser Outside diameter