






eco-fix · eco-fix^{plus}

	APPLICATION	PRODUCT LINES
Part No.: K550422-10 Weight 20 g Pin connector Ø 6 mm eco-fix^{plus} For e.g., as a rotating joint in connection with Ø 12 mm location pin K551042.  		eco-fix eco-fix^{plus}
Part No.: K550592-10 L = 20 mm, Weight 5 g K550557-10 L = 25 mm, Weight 6 g Threaded bolt M6 eco-fix^{plus} For the connection of threaded eco-fix^{plus} location pins.  	K550557-10  K550592-10 	eco-fix^{plus}
Part No.: K551332 Weight 150 g Articulated stand S In connection with damping hand K551336 or mounting brackets for quick and easy positioning of workpieces in the measuring volume of the CMM.  		eco-fix eco-fix^{plus}
Part No.: K551303 Weight 460 g Articulated stand M In connection with damping hand K551336 or mounting brackets for quick and easy positioning of workpieces in the measuring volume of the CMM.  		eco-fix eco-fix^{plus}
Part No.: K551335 Weight 980 g Articulated stand L Directly mount M6 components or use mounting bracket K551045 for quick and easy positioning of workpieces in the measuring volume of the CMM.  		eco-fix eco-fix^{plus}