



TRACKSCAN SHARP-S

TrackScan Sharp-S Optical 3D Scanning System, engineered with 25-megapixel industrial cameras and robust onboard processors for edge computing, is specially designed for measuring large-scale parts over a long distance with high speed. It brings optical measurements to new heights by offering a tracking distance of up to 8.5 meters, a high-precision measurement range of 135 m³, enabling powerful measurement experiences.

Long-distance and Large-volume Tracking

- Tracking distance as long as 8.5 meters.
- 135-m³ industrial high-precision measurement range.
- Saves the hassle of moving trackers frequently.
- Measure large components efficiently in just one position.

Excellent and Stable Performance

- A maximum volumetric accuracy of 0.048 mm (10.4 m³).
- Lightweight and stable structure with CFFIM technology.
- Unaffected by thermal variations to ensure high-precision measurements.
- Hand it over and position it freely.

Precise Detail Capture

- 17 parallel laser lines.
- Scan over a large area.
- Provides exceptional detail-capturing efficiency.
- Capture intricate details such as slots and angles with high precision and speed.

Wireless and Easy 3D Scanning

- Powerful onboard processors for edge computing.
- With batteries, and external network cards.
- Measure objects wirelessly.
- Plug-and-play.
- User-friendly operation.

Fast 3D Scanning

- Scans up to an impressive 4.86 million measurements/s.
- 81 blue laser lines.
- Ideal to capture 3D data and identify deviations of parts rapidly.
- Facilitates more efficient and intelligent measurements for manufacturers.

Versatile Compatibility

- Intelligent edge detection.
- i-Probe500.
- Multi-tracker measurement.
- Automated measurement.

Technical Specifications

Type		TrackScan Sharp-S
Scan mode	Ultra-fast scanning	81 blue laser lines (Triple Cross Technology)
	Hyperfine scanning	17 blue parallel laser lines
	Deep-hole scanning	Extra 1 blue laser line
Accuracy ⁽¹⁾		up to 0.025 mm
Measurement rate up to		4,860,000 measurements/s
Scanning area up to		800 mm × 700 mm
Laser class		Class II (eye-safe)
Resolution up to		0.020 mm
Volumetric accuracy ⁽²⁾	10.4 m ³ (3.5 m)	0.048 mm
	35 m ³ (5.2 m)	0.069 mm
	90 m ³ (7.2 m)	0.128 mm
	135 m ³ (8.5 m) ⁽³⁾	0.159 mm
Volumetric accuracy (with MSCAN photogrammetry system)		0.044 mm + 0.012 mm/m
Stand-off distance		300 mm
Depth of field		400 mm, 800 mm (Large depth of field)
Hole position accuracy		0.050 mm
Output format		.stl, .pj3, .igs, .asc and etc., customized
Operating temperature range		-10–40 °C
Operating humidity range (non-condensing)		10-90 % RH
Interface mode		USB 3.0, Network Interface
Certification		CE, Rohs, WEEE, FCC
Patents		CN109000582B, CN110992393B, CN111678459B, CN111694665B, CN112802002B, CN112867136B, CN112964196B, CN113188476B, CN113340234B, CN113432561B, CN113473034B, CN113514008B, CN113766083B, CN114001696B, CN114205483B, CN114554025B, CN114627249B, CN115289974B, CN115325959B, CN115493512B, CN115511688B, CN115661369B, CN115690333B, CN115695763B, CN116136396B, CN116206069B, CN116244730B, CN209263911U, CN210567185U, CN211121096U, CN214149174U, CN218103220U, CN218103238U, CN218411072U, CN218584004U, CN218734448U, CN219829788U, CN219834226U, CN307756797S, EP3392831B1, EP3907702B1, KR102096806B1, US10309770B2, US11060853B2, US11493326B2

(1) ISO 17025 accredited: Based on VDI/VDE 2634 Part 3 standard and JJF 1951 specification, probing error (size) (PS) performance is evaluated.

(2) ISO 17025 accredited: Based on VDI/VDE 2634 Part 3 standard and JJF 1951 specification, sphere spacing error (SD) performance is evaluated.

(3) The industrial-grade high-precision measurement range of TrackScan Sharp-S is up to 135 m³, and its scanning range is up to 233 m³.

